

The data shown is all the metadata we could automatically extract from your file. It may be neither complete nor adequate. Metadata could have been changed or deleted in the past. Please be aware that the metadata is provided without liability.

Metadata of R6P_8424

Checksum	96bc0d9457cc7ffb2bb10bccfb06c390
Filename	R6P_8424.JPG
Filesize	4.0 MB
Filetype	JPEG
Filetypeextension	jpg
Mimetype	image/jpeg
Exifbyteorder	Little-endian (Intel, II)
Make	Canon
Model	Canon EOS R6
Orientation	Horizontal (normal)
Xresolution	72
Yresolution	72
Resolutionunit	inches
Modifydate	2025:05:22 15:06:04
Artist	Pieter Dhaeze
Ycbcrpositioning	Co-sited
Copyright	info@dhaeze.nl
Exposuretime	1/250
Fnumber	11
Exposureprogram	Shutter speed priority AE
Iso	400
Sensitivitytype	Recommended Exposure Index

Metadata of R6P_8424

Recommendedexposureindex	400
Exifversion	231
Datetimeoriginal	2025:05:22 15:06:04
Createdate	2025:05:22 15:06:04
Offsettime	+02:00
Offsettimeoriginal	+02:00
Offsettimedigitized	+02:00
Componentsconfiguration	Y, Cb, Cr, -
Shutterspeedvalue	1/256
Aperturevalue	11.3
Flash	No Flash
Focallength	600.0 mm
Macromode	Normal
Selftimer	Off
Quality	Fine
Canonflashmode	Off
Continuousdrive	Single
Focusmode	One-shot AF
Recordmode	JPEG
Canonimagesize	Large
Easymode	Manual
Digitalzoom	None
Contrast	Normal
Saturation	Normal
Cameraiso	Auto
Meteringmode	Evaluative
Focusrange	Auto
Canonexposuremode	Shutter speed priority AE

Metadata of R6P_8424

Lenstype	Canon RF 50mm F1.2L USM or other Canon RF Lens
Maxfocallength	600 mm
Minfocallength	600 mm
Focalunits	1/mm
Maxaperture	11
Minaperture	11
Flashactivity	0
Flashbits	E-TTL
Focuscontinuous	Single
Imagestabilization	On (2)
Zoomsourcewidth	0
Zoomtargetwidth	0
Manualflashoutput	n/a
Colortone	Normal
Clarity	-3
Focaltype	Fixed
Autoiso	100
Baseiso	400
Measuredev	13.25
Targetaperture	11
Targetexposuretime	1/256
Exposurecompensation	0
Whitebalance	Auto
Slowshutter	None
Sequencenumber	0
Opticalzoomcode	n/a
Cameratemperature	24 C

Metadata of R6P_8424

Flashguidenumber	0
Flashexposurecomp	0
Autoexposurebracketing	Off
Aebbracketvalue	0
Controlmode	Camera Local Control
Measuredev2	28.5
Bulbduration	0
Cameratype	EOS High-end
Autorotate	None
Ndfilter	Off
Canonimagetype	Canon EOS R6
Canonfirmwareversion	Firmware Version 1.9.0
Shuttercount	34516
Canonmodelid	EOS R6
Thumbnailimagevalidarea	0 159 6 113
Afareamode	Spot AF
Numafpoints	1053
Validafpoints	1
Canonimagewidth	5472
Canonimageheight	3648
Afimagewidth	5472
Afimageheight	3648

Metadata of R6P_8424

Afareawidths

[illegible]

www.metadata2go.com Page 5

Metadata of R6P_8424

Afareaheights

[illegible]

```
v.metadata2go.com                                     Page 7
```


Metadata of R6P_8424

Afareaxpositions

[illegible][illegible]

Metadata of R6P_8424

Afareaypositions

-238 000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

00000000000000000000000000000000

Metadata of R6P_8424

Afpoinstsinfocus	0
Afpointssselected	0
Imageuniqueid	efed4d088182447e93694c8ceddd2321
Timezone	+02:00
Timezonecity	Paris
Daylightsavings	On
Batterytype	LP-E6NH
Bracketmode	Off
Bracketvalue	0
Bracketshotnumber	0
Rawjpgsize	Large
Wbbracketmode	Off
Wbbracketvalueab	0
Wbbracketvaluegm	0
Liveviewshooting	On
Focusdistanceupper	7.46 m
Focusdistancelower	6.87 m
Shuttermode	Electronic
Flashexposurelock	Off
Antiflicker	Off
Rflenstype	Canon RF 600mm F11 IS STM
Internalserialnumber	KQ0024655
Dustremovaldata	(Binary data 1024 bytes)
Cropleftmargin	0
Croprightmargin	0
Croptopmargin	0
Cropbottommargin	0
Exposurelevelincrements	1/3 Stop

Metadata of R6P_8424

Isospeedincrements	1/3 Stop
Aebautocancel	On
Aebsequence	0,-,+
Aebshotcount	3 shots
Safetyshift	Disable
Shutterspeedrange	Manual: Hi 1/8123; Lo 31.9; Auto: Hi 1/8123; Lo 0.5
Aperturerange	Manual: Closed 64; Open 1; Auto: Closed 9.4; Open 9.4
Sameexposurefornewaperture	Disable
Aelockmetermodeafterfocus	Evaluative
Dialdirectiontvav	Normal
Customcontrols	19 0 4 0 0 65535 65535 65535 72 0 0 65535 65535 65535 59 0 4 0 90 0 25 0 7 0 13 0 122 2 14 2 5 0 29 0 76 0 75 0 75 0 76 0 23 0 0 0 0 90 0 29 0 54 0 78 0 92 0 103 0 39 0 105 0 53 0 254014 0 3 5376 3840 0 0 0 0 0 0 0 0 0 0 5200 0 0 1 64 0 0 0 0 0 65535 0 7 3 4 31 1 2 3 4 5 1
Shutterreleasewithoutlens	Enable
Controlringrotation	Normal
Addaspectratioinfo	Off
Defaultteraseoption	Cancel selected
Retractlensonpoweroff	Enable
Addiptcinformation	Disable
Audiocompression	Enable
Aspectratio	3:2
Croppedimagewidth	5472
Croppedimageheight	3648
Croppedimageleft	0

Metadata of R6P_8424

Croppedimagetop	0
Tonecurve	Standard
Sharpness	4
Sharpnessfrequency	n/a
Sensorredlevel	0
Sensorbluelevel	0
Whitebalancered	0
Whitebalanceblue	0
Colortemperature	4000
Picturestyle	Standard
Digitalgain	0
Wbshiftab	0
Wbshiftgm	0
Unsharpmaskfineness	2
Unsharpmaskthreshold	3
Measuredrggb	578 1024 1024 609
Vrdoffset	0
Sensorwidth	5568
Sensorheight	3708
Sensorleftborder	84
Sensortopborder	50
Sensorrightborder	5555
Sensorbottomborder	3697
Blackmaskleftborder	0
Blackmasktopborder	0
Blackmaskrightborder	0
Blackmaskbottomborder	0
Colordataversion	33 (R5/R6)

Metadata of R6P_8424

Wb Rggblevelsasshot	1931 1024 1024 1649
Colortempasshot	5212
Wb Rggblevelsauto	1931 1024 1024 1649
Colortempauto	5212
Wb Rggblevelsmeasured	1931 1024 1024 1649
Colortempmeasured	5212
Wb Rggblevelsdaylight	1872 1024 1024 1611
Colortempdaylight	5200
Wb Rggblevelsshade	2166 1024 1024 1387
Colortempshade	7000
Wb Rggblevelscloudy	2024 1024 1024 1492
Colortempcloudy	6000
Wb Rggblevelstungsten	1321 1024 1024 2346
Colortemptungsten	3200
Wb Rggblevelsfluorescent	1570 1024 1024 2265
Colortempfluorescent	3631
Wb Rggblevelskelvin	1586 1024 1024 1938
Colortempkelvin	3992
Wb Rggblevelsflash	2068 1024 1024 1467
Colortempflash	6259
Perchannelblacklevel	2047 2047 2047 2047
Normalwhitelevel	13535
Specularwhitelevel	14888
Linearityuppermargin	12735
Picturestyleuserdef	Standard; Standard; Standard
Picturestylepc	None; None; None
Custompicturestylefilename	
Afmicroadjmode	Disable

Metadata of R6P_8424

Afmicroadjvalue	0
Vignettingcorrversion	96
Peripherallightingsetting	On
Chromaticaberrationsetting	On
Distortioncorrectionsetting	On
Digitallensoptimizersetting	Off
Peripheralilluminationcorr	Off
Autolightingoptimizer	Standard
Highlighttonepriority	Off
Longexposurenoisereduction	Off
Highisonoisereduction	Standard
Digitallensoptimizer	Off
Dualpixelraw	Off
Ambienceselection	Standard
Multiexposure	Off
Multiexposurecontrol	Additive
Multiexposureshots	0
Hdr	Off
Hdreffect	Natural
Afconfigtool	Case 11
Aftrackingsensitivity	127
Afacceldeceltracking	127
Afpointswitching	-1
Aiservofirstimage	Equal Priority
Aiservosecondimage	Equal Priority
Usmlenselectronicmf	Disable After One-Shot
Afassistbeam	Enable
Oneshotafrelease	Focus Priority

Metadata of R6P_8424

Autoafpointseleositraf	Enable
Lensdrivewhenafimpossible	Continue Focus Search
Selectafareaselectionmode	Single-point AF, Auto, Zone AF, AF Point Expansion (4 point), Spot AF, AF Point Expansion (8 point), [6], [8], [9], [10], [11], [12], [13], [14]
Afareaselectionmethod	Main Dial
Orientationlinkedaf	Same for Vert/Horiz Points
Manualafpointselfpattern	Stops at AF Area Edges
Afpointdisplayduringfocus	Selected (constant)
Vfdisplayillumination	Auto
Afstatusviewfinder	Show in Field of View
Initialafpointinservo	Initial AF Point Selected
Subjecttodetect	None
Eyedetection	Off
Usercomment	
Subsectime	35
Subsectimeoriginal	35
Subsectimedigitized	35
Flashpixversion	100
Colorspace	sRGB
Exifimagewidth	5472
Exifimageheight	3648
Interopindex	R98 - DCF basic file (sRGB)
Interopversion	100
Focalplanexresolution	3872.611465
Focalplaneyresolution	3872.611465
Focalplaneresolutionunit	inches
Customrendered	Normal

Metadata of R6P_8424

Exposuremode	Auto
Scenecapturetype	Standard
Ownername	
Serialnumber	43021000493
Lensinfo	600mm f/0
Lensmodel	RF600mm F11 IS STM
Lensserialnumber	0000003b99
Gpsversionid	2.3.0.0
Compression	JPEG (old-style)
Thumbnailoffset	30720
Thumbnaillength	8732
Rating	0
Mpfversion	100
Numberofimages	2
Mpimageflags	Dependent child image
Mpimageformat	JPEG
Mpimagetype	Large Thumbnail (full HD equivalent)
Mpimagelength	171147
Mpimagestart	3812352
Dependentimage1entrynumber	0
Dependentimage2entrynumber	0
Imagewidth	5472
Imageheight	3648
Encodingprocess	Baseline DCT, Huffman coding
Bitspersample	8
Colorcomponents	3
Ycbcrsubsampling	YCbCr4:2:2 (2 1)
Conditionalfec	0

Metadata of R6P_8424

Drivemode	Single-frame Shooting
Flashtype	Built-In Flash
Lens	600.0 mm
Redeyereduction	Off
Shootingmode	Shutter speed priority AE
Shuttercurtainhack	1st-curtain sync
Wb Rggblevels	1931 1024 1024 1649
Aperture	11
Bluebalance	1.610352
Imagesize	5472x3648
Lensid	Canon RF 600mm F11 IS STM
Megapixels	20
Redbalance	1.885742
Scalefactor35efl	1
Shutterspeed	1/250
Subseccreatedate	2025:05:22 15:06:04.35+02:00
Subsecdatetimeoriginal	2025:05:22 15:06:04.35+02:00
Subsecmodifydate	2025:05:22 15:06:04.35+02:00
Thumbnailimage	(Binary data 8732 bytes)
Previewimage	(Binary data 171147 bytes)
Lens35efl	600.0 mm (35 mm equivalent: 601.8 mm)
Circleofconfusion	0.030 mm
Dof	0.09 m (7.12 - 7.21 m)
Fov	3.4 deg
Focallength35efl	600.0 mm (35 mm equivalent: 601.8 mm)
Hyperfocaldistance	1092.56 m
Lightvalue	12.9
Category	image

Metadata of R6P_8424

Raw Header

FF D8 FF E1 9B FC 45 78 69 66 00 00 49 49 2A 00
08 00 00 00 0C 00 0F 01 02 00 06 00 00 00 9E 00 00
00 10 01 02 00 0D 00 00 00 A4 00 00 00 12 01 03 00
01 00 00 00 01 00 00 00 1A 01 05 00 01 00 00 00 C4
00 00 00 1B 01 05 00 01 00 00 00 CC 00 00 00 28 01
03 00 01 00 00 00 02 00 00 00 32 01 02 00 14 00 00
00 D4 00 00 00 3B 01 02 00 0E 00 00 00 E8 00 00 00
13 02 03 00 01 00 00 00 02 00